



LTO

EXTENSIVE RANGE

SPORT SERIES

GO THE DISTANCE WITH THE 2WD BAD BOY LTO – THE ONLY SPORT SERIES VEHICLE AVAILABLE WITH A GAS ENGINE FOR EXTENDED RANGE. YOU CAN ALSO OPT FOR A 48-VOLT ELECTRIC MODEL FOR STEALTHY OPERATION. EACH MODEL FEATURES AN 800-LB TOTAL CAPACITY, SEATING FOR FOUR AND A REAR-FACING SEAT THAT CONVERTS TO A SPACIOUS CARGO DECK FOR MAXIMUM FLEXIBILITY.



BADBOYBUGGIES.COM

LTO

EXTENSIVE RANGE



SIDE



FRONT

STANDARD EQUIPMENT

- Front brush guard
- Rear-facing seat/cargo deck combo
- Headlight
- Horn
- State of Charge Meter (electric model)
- Fuel Gage (gas model)

OPTIONS & FIELD-INSTALLED ACCESSORIES

- Terra Trac Tires (22 x 11-10) w/ Polished Spoke Wheels
- Turf Saver® Tires (20 x 10-10) 4 Ply Rated
- Stryker® Tires (22 x 9-10) Uni-directional STD
- Speed Racer Tires (18 x 10-10) on Diamond Wheels
- Front Basket
- Floor Mounted Gun Rack
- Taillights
- Battery Maintenance System (electric)
- Limited Slip Differential
- 12-Volt Accessory Outlet (gas)
- Turn Signals w/ 4-way Flashers
- Roof
- Windshield
- Rearview Mirror
- Locking Glovebox(es)
- Weather Enclosure

POWER	ELECTRIC	GAS
MOTOR	48-Volt DC Shunt Wound	4 Cycle (401 cc), Single-Cylinder OHV with Hemispheric Combustion Chamber
HORSEPOWER (FRONT)	N/A	N/A
HORSEPOWER (REAR)	14.5 HP at Maximum Torque	13 HP
DRIVE TRAIN	Motor Shaft Direct Drive	Continuous Variable Transmission
BATTERIES	Six, Deep Cycle 8-Volt Batteries	One, 12-Volt Maintenance Free
CHARGE TIME	8-10 Hours to Fully Charge (Results May Vary)	N/A
DIFFERENTIAL	Open Differential with Helical Gears	Open Differential with Helical Gears
RATIO	14.76:1	11.42:1 (forward) 15.78:1 (reverse)
STEERING & SUSPENSION		
TIRES	Trail Wolf® Uni-Directional (22 x 11-10)	Trail Wolf® Uni-Directional (22 x 11-10)
FRONT SUSPENSION	Leaf Spring with Hydraulic Shocks	Leaf Spring with Hydraulic Shocks
REAR SUSPENSION	Leaf Spring with Hydraulic Shocks	Leaf Spring with Hydraulic Shocks
PERFORMANCE		
CARGO BED CAPACITY	250 lb	250 lb
FRONT RACK	N/A	N/A
ROOF RACK	N/A	N/A
TOWING CAPACITY	N/A	N/A
TOTAL CAPACITY (w/ PASSENGERS)	800 lb	800 lb
BRAKING		
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum	Rear Wheel Mechanical Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single-Point Engagement	Self-Compensating, Single-Point Engagement
DIMENSIONS		
WHEELBASE	66.0 in	66.0 in
LENGTH	107.0 in	107.0 in
WIDTH	49.0 in	49.0 in
HEIGHT	52.0 in (75.0 in w/ Optional Roof)	49.0 in (72.0 in w/ Optional Roof)
WEIGHT	1,040 lb	1,006 lb
TURNING DIAMETER	19.0 ft (Outside Clearance Circle)	20.0 ft (Outside Clearance Circle)
GROUND CLEARANCE (UNDER AXLE)	6.0 in	6.0 in
COLORS		
STANDARD CAMOUFLAGE	Realtree® AP™	Realtree® AP™
AVAILABLE UPGRADES	- Black - Bright White - Forest Green - Flame Red - Patriot Blue	- Black - Bright White - Forest Green - Flame Red - Patriot Blue